

Pureflo Product Range – CTU Vessels

12 different combinations available



Product Code PF CTU5 PF CTU10 PF CTU20 PF CTU30

Applications

- Boilers and hot taps
- Coffee machines
- Vending machines
- Combi steamers
- Steam cookers and ovens

Head: 15mm post with selective 30%, 40% or 50% bypass and flush valve

Specifications

	PF CTU5	PF CTU10	PF CTU20	PF CTU30
Housing Volume (litres)	5	10	20	30
Certification	WRAS*	WRAS*	WRAS*	WRAS*
Dimensions H x W (mm, ex head)	33 x 15	43 x 20	89 x 20	112 x 20
Flow Rate (litres/min)	2 - 6	2 - 6	2 - 6	2 - 6
Temperature Range (°C)	2 - 35	2 - 35	2 - 35	2 - 35
Max pressure (bar)	6	6	6	6
Capacity (litres)				
At 30% bypass	8,100	16,200	32,400	46,800
At 40% bypass	9,100	18,100	36,300	52,400
At 50% bypass	10,000	20,000	40,000	58,000

nb. Subject to inlet water pressure

* Certification pending

Media available

Media **	PF CTU5	PF CTU10	PF CTU20	PF CTU30
Resin Carbon	X	X	X	X
Resin "Fibredyne"	X	X	X	X
Resin Nano	X	X	X	X

**Media insert available with and without NSF certified polyphosphate beads for scale reduction